

# TECHNICAL DATA SHEET



**Product code:** 8376 **Sector:** Automotive (Passenger car & LCV) **Issue No:** 4 **Issue Date:** 01/05/23

## XF Premium MTF 75w90

Fully synthetic gear oil for use in gearboxes, transfer cases & differentials.

### Application

A premium OEM gear oil formulated using the latest technology for gearbox applications requiring a 75w90 viscosity. Predominantly for European and Asian manufacturers.

### Suitable for

API GL-4, GL-5

BMW Group Inc. Mini, Rolls Royce MTF LT-4, OSP  
Fiat Chrysler Automobiles Inc. Abarth, Alfa Romeo,  
Dodge, Ferrari, Jeep, Lancia, Maserati (pre-2021)  
9.55550-MZ11, 9.55550-DA7  
Ford M2C203-A1, M2C201-A, M2C200-C (BOT  
130),  
M2C200-B, M2C197-A, M2C175-A, N052145 VX00  
General Motors Inc. Buick, Cadillac, Chevrolet,  
GMC, Opel, Saturn, Vauxhall (pre-2017),  
GM 89021806/89021807, GM 89021677/89021678,  
GM 88900401/89021678, GM 1940757,  
GM 19351882/19351883, GM 9986285  
Jaguar XH-21  
Mercedes-Benz MB 235.8, 235.72, 235.0  
Volvo 97309  
VW Group Inc. Audi, Seat, Skoda,  
Bentley, Lamborghini,  
G51, G50, P/N G 005 000,  
TL 529 11 P/N G 052 911,  
TL 521 45 P/N G 052 145,  
TL 501 50 P/N G 050 150,  
Porsche P/N 999.917.546.00,  
P/N 999.917.067.00, P/N 000.043.210.12,  
P/N 000.043.207.76, P/N 000.043.204.20,  
P/N 000.043.204.19

BOT 328, BOT 130

### Features & Benefits

- XF Premium gear oil provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the gearbox from the very start of every journey.
- XF Premium gearbox oil maximises viscosity stability at high temperatures. This reduces gearbox wear giving superior component protection including gear teeth, shafts and bearings.
- Delivers outstanding lubrication and instant protection under hot and cold temperatures.
- XF Premium gear oil is specifically formulated for use in hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).

### Typical Characteristics

Density @ 15°C, g/ml	0.865
Kinematic Viscosity @ 100°C, cSt	14.0
Flash Point, °C	>220

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

**Footnotes:** P/N – OEM Part Number



**MADE IN BRITAIN**

**Millers Oils Ltd**  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)