

TECHNICAL DATA SHEET



Product code: 5305

Sector: Industrial

Issue No: 2

Issue Date: 12/05/22

DELTAPLEX 2EP

A lithium complex grease of outstanding performance and a distinctive red in colour.

Application

A universal grease suitable for all anti-friction and plain bearings and highly suitable for the lubrication of universal joints.

Performance Profile

- Good mechanical stability and added tenacity.
- Extreme pressure (EP) properties generate excellent load carrying characteristics.
- Good performance over a wide temperature range.
- Excellent resistance to corrosion.

Typical Characteristics

Appearance	Red Smooth Adhesive Grease
NLGI Classification	2
Thickener	Lithium Complex Soap
Solid Lubricant	n/a
Base Oil	Mineral Oil
Base Oil Viscosity @40°C	180cSt
Worked Penetration (IP50)	265 to 295
Drop Point (IP132) °C	250 minimum
Copper Corrosion (IP112)	Pass
Emcor (IP 220) Corrosion Test	00:00
Four Ball Weld Load (IP239)	450kgs
Timken OK Load (IP326)	20kgs (45lbs)
Operating Temperature Range °C	-20 to +150

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk



MADE IN BRITAIN

Millers Oils Ltd

Brighouse West Yorkshire HD6 3DP UK

Tel: +44(0) 1484 713201

www.millersoils.co.uk